GUELPH PERMEAMETER ATTACHMENTS







2805D20 Ring Attachment, 20 cm

GUELPH PRESSURE INFILTROMETER RING ATTACHMENTS

Model 2805D10 Ring Attachment, 10 cm

Model 2805D10 provides extended ability of the 2800K1 Guelph Permeameter to measure infiltration (K_{fs}) and matrix flux (\emptyset_m) in soils using a ring 10 cm in diameter for the retained pressure heads. For use in materials having hydraulic conductivities of 10^{-3} to 10^{-6} cm/s. Comes complete with replaceable Cutting Ring, Support Ring, Transparent Cover, and Installation Ring.

Specifications:

Head Height Range: 0 to 250 mm

Insertion Marking: 1 cm intervals, 5 cm maximum

Net Weight: 3.7 lbs.

Model 2805D20 Ring Attachment, 20 cm

Model 2805D20 provides extended ability of the 2800K1 Guelph Permeameter to measure infiltration (K_{fs}) and matrix flux (\emptyset_{m})in soils using a ring 20 cm in diameter for the retained pressure heads. Recommended for hydraulic conductivities of 10^{-3} to 10^{-7} cm/s. Comes complete with replaceable Cutting Ring, Support Ring, Transparent Cover, and Installation Ring.

Specifications:

Head Height Range: 0 to 250 mm

Insertion Marking: 1 cm intervals, 5 cm maximum

Net Weight: 7.9 lbs.

© Copyright Soilmoisture Equipment Corp. 1998 All rights reserved 0899-2805 (07/98)

SOILMOISTURE EQUIPMENT CORP.

801 S. Kellogg Ave., Santa Barbara, CA 931117 Phone: (805) 964-3525 - Fax (805) 683-2189

e-mail: sales@soilmoisture.com Web: http://www.soilmoisture.com

